



Dry Flake Applied Wall Coating
69 Cleveland Avenue
Bay Shore, NY 11706
Phone: 877 253 6373
Fax: 631 242 7327
E-mail: info@BLENDS.us
www.BLENDS.us

BLENDS DRY FLAKE APPLIED WALL COATING CLEANING and MAINTENANCE INSTRUCTIONS

Proper cleaning and maintenance will keep the BLENDS finish looking new.

The BLENDS topcoat allows for frequent cleaning. Remove ordinary dirt with a soft cloth and a mild detergent solution. A soft brush may be used.

For more difficult stains, Citri Clean or an equivalent citrus based cleaner may be used. Follow the manufacturers label instructions and start with the mildest recommended dilution. Spot test an inconspicuous area when increasing the concentration.

Staining agents should be removed immediately to help reduce the possibility of spreading soiled areas or the "setting" of the stain.

Read all manufacturers instructions before using other cleaning products. Cleaning solutions should be compatible with acrylic paint composition.

BLENDS is easy to touch up. Bleeding staining agents such as dye based felt markers should first be sealed with BLENDS UNIVERSAL PRIMER (a stain blocking sealer). When the sealer is dry apply the appropriate BLENDS Basecoat in a 10 mil wet coat, feathering the edges of the repaired area. Immediately apply flakes by blowing them from the palm of your hand into the wet basecoat. Allow the basecoat to dry, brush off the loose flakes, and apply BLENDS TOPCOAT by brush or roller, feathering the edges beyond the repaired margin.

04.08.08